



## VACUUM GAUGE

Series	
10	

Series	
11	

## VACUUM SWITCH

Series	Description	
21	0+0,8 bar (0+80 kPa) SPDT, adjustable	
90	0,3 bar (30 kPa) N.O.	
92	0,3 bar (30 kPa) N.C.	

Max voltage 220 Vca 50-60 Hz, max current 0,5 A resistive, 0,25 A inductive, switching power 100 VA, protection IP65.

Series	Description	
L1	0,2 bar (20 kPa) SPDT	
91		

Max voltage 250V – 50 Hz, max current 6 A resistive, 1 A inductive, protection IP65.

## PRESSURE GAUGE

Series	Description	
30	0+6 bar (0+600 kPa)	
32	0+6 bar (0+600 kPa)	

Series	Description	
31	0+12 bar (0+1,2 MPa)	

## PRESSURE SWITCH

Series	Description	
P1	SPDT 1,5 bar (150 kPa)	
P6	2 bar (200 kPa)	

Max voltage 250V – 50 Hz, max current 6 A resistive, 1 A inductive, protection IP65.

Series	Description	
80	1,5 bar (150 kPa) N.O.	
81	1,5 bar (150 kPa) N.C.	
84	1,3 bar (130 kPa) N.O.	
85	1,3 bar (130 kPa) N.C.	
86	2 bar (200 kPa) N.O.	
87	2 bar (200 kPa) N.C.	

Max voltage 220 Vca 50-60 Hz, max current 0,5 A resistive, 0,25 A inductive, switching power 100 VA, protection IP65.

# CLOGGING INDICATORS



Pressure Indication



Differential Pressure Indication

Summing up

## VISUAL - FOR PE SERIES ONLY - ELECTRICAL

Series	Description	
UO	1,3 bar (130 kPa)	

Series	Description	
N0	1,3 bar (130 kPa)	

## VISUAL ELECTRICAL (\*)

Series	Description	
5B	1,3 bar (130 kPa)	
5C	2 bar (200 kPa)	
5D	2,5 bar (250 kPa)	
5E	5 bar (500 kPa)	
5F	8 bar (8000 kPa)	

Series	Series with LED (*)	Description	
6B	7B	1,3 bar (130 kPa)	
6C	7C	2 bar (200 kPa)	
6D	7D	2,5 bar (250 kPa)	
6E	7E	5 bar (500 kPa)	
6F	7F	8 bar (800 kPa)	

## ELECTRICAL WITH THERMOSTAT ELECTRICAL + VISUAL

Series	Description	
T0	1,3 bar (130 kPa)	
T1	2 bar (200 kPa)	
T2	5 bar (500 kPa)	
T3	8 bar (800 kPa)	
T6	2,5 bar (250 kPa)	

(Series available on request only)

Series	Description	
70	1,3 bar (130 kPa)	
71	2 bar (200 kPa)	
72	5 bar (500 kPa)	
73	8 bar (800 kPa)	
76	2,5 bar (250 kPa)	

(Series available on request only)

For indicators 6+ - 7+ - T+ - N0  
SPDT differential switch

C.A. 125-250 V:  
> max resistive or inductive load 1 A

C.C. 14 - 30 V:  
> max resistive or inductive load 4 - 3 A respectively

Protection IP65  
Connector DIN 43650

Differential indicators:  
Recommended tightening torque 90 Nm